

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 December 2004 (02.12.2004)

PCT

(10) International Publication Number
WO 2004/105169 A1

(51) International Patent Classification⁷: H01M 8/04
(21) International Application Number:
PCT/JP2004/005103

(22) International Filing Date: 9 April 2004 (09.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-147996 26 May 2003 (26.05.2003) JP

(71) Applicant (for all designated States except US): NISSAN
MOTOR CO., LTD. [JP/JP]; 2, Takara-cho, Kana-
gawa-ku, Yokohama-shi, Kanagawa 2210023 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): IIO, Masatoshi
[JP/JP]; 7-38-31, Ikegami, Yokosuka-shi, Kanagawa
2380035 (JP).


(74) Agent: GOTO, Masaki; Shoyu-Kaikan 3-1, Kasumi-
gaseki 3-chome, Chiyoda-ku, Tokyo 1000013 (JP).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG,
KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: ANODE EFFLUENT CONTROL IN FUEL CELL POWER PLANT



(57) Abstract: A fuel cell stack (1) performs power generation using an anode gas having hydrogen as its main component, and after a power generation reaction, the anode gas is discharged as anode effluent. The anode effluent is re-circulated into the anode gas through a return passage (5). The return passage (5) comprises a purge valve (8) which discharges the anode effluent to the outside of the passage. In this invention, calculation of a first energy loss caused by an increase in non-hydrogen components in the anode gas while the purge valve (8) is closed (S7, S28), and calculation of a second energy loss which corresponds to the amount of hydrogen lost from the anode gas by opening the purge valve (8) (S8, S29) are performed. By opening the purge valve (8) when the second energy loss equals or falls below the first energy loss, the start timing of purging is optimized.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

— with international search report